

XL HYDRAULIC DETACHABLE EXTENDABLE



- 28' 7" deck extends to 49' 11" to handle long loads
- · Gooseneck offers 7 position variable ride height
- Hydraulic neck for faster loading and unloading
- Frame reinforcement for flip axle/booster
- Extension stops every two feet
- Brackets for 36" flip neck
- Optional lockable tool box in neck



XL 80 HDE EXTENDATIAS SPECIALIZED STRAILENGED SPECIALIZED SPECIALI


RUGGED & VERSATILE MAIN DECK


The XL 80 & 90 HDE deck is fully equipped for versatile hauling, with (14) 1/2" chain drops per side, 8 bent D-rings per side, and removable swing out outrigger brackets on 24" centers. The rugged Apitong decking stands up to years of wear and tear.

THE LEADER IN EXTENDABLE TRAILERS

The patented XL Extend-A-Trac allows for extending and retracting the trailer without hooking and unhooking air and electrical lines. Open the trailer to various lengths, using the extension stops every two feet. 6" greaseable rollers incorporate oil impregnated bronze bushings to make extending easy. The new one-piece track pan design adds stability.

DESIGNED FOR YOU. BUILT TO LAST.





IDE SPECS

8



XL 80 HDE CAPACITY

capacity: 80,000 lb overall concentrated: 60,000 lb in 10' closed

XL 90 HDE CAPACITY

capacity: 90,000 lb overall concentrated: 70,000 lb in 10' closed

OVERALL LENGTH & WIDTH

overall length: 48' - 69' 4" overall width: 102"

GOOSENECK

hydraulic detachable (narrow)
10' 5" long
49" 5th wheel height
84" swing clearance
16" king pin setting with 3/8" plate
7 position variable ride height
hydraulics run off wet kit
air operated lock with manual
safety latch
brackets for 36" flip neck

GOOSENECK OPTIONS

toolbox in rear of neck w alum. door 13HP power unit, base of neck, aluminum cover, dual hydraulics registration holder 36" flip neck

MAIN DECK

28' 7" - 49' 11" long patented extend-a-trac extension stops on 24" centers T-1 flange, 80K web (4) 14" fabricated i-beams 20" loaded deck height 6" ground clearance formed cross members on 12" centers 8 bent d-rings per side 1 1/8" Apitong decking - flush, center covered ramp tapers to 4" (14) 1/2" chain drops per side removable swing out outrigger brackets on 24" centers 2 flag holders at front 54" axle spacing: 30" long mini-deck 60"axle spacing: 24" long mini-deck

MAIN DECK OPTIONS

storage compartment in rear of main deck (mini deck) removable swing out outriggers oak outrigger planks, 2" x 10" 1 3/8" apitong decking - raised additional clearance lights 4-way plugs

REAR BRIDGE

54" axle spacing: 9' Long
60" axle spacing: 9' 6" Long
40" deck height
1 1/8" Apitong decking - flush
2 flag holders
2 stake pockets in tail channel
2 pan style d-rings per side, on
corner
66" wide bumper at rear
80: frame reinforcement
for flip axle
90: frame reinforcement for

REAR BRIDGE OPTIONS

2 axle booster

1 pair clearance lights
pull out lights
4" amber strobe tail light
additional tail light
battery back up
(1) 4-way plug
1 3/8" Apitong decking - raised
dock bumpers

SUSPENSION

25,000 lb air ride raise and lower valve manual ride height control

SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale

AXLES

(2) 25,000 lb nominal hub pilot, outboard drums 4S2M ABS 16 1/2" x 7" brakes 2 pair spring brakes

AXLE OPTIONS

PSI tire inflation system
hubometer
TP axles (same inner & outer bearings)
limit straps
dust shields
cam covers

WHEELS & TIRES

8.25 x 22.5 steel rims 255 / 70R / 22.5 tires

WHEEL & TIRE OPTIONS

aluminum mill wheels (inside)
aluminum mill wheels (outside)
aluminum polished wheels (outside)
aluminum Durabright wheels (outside)
Michelin 255/70R/22.5 tires
Goodyear 275/70R/22.5 tire
(41" rear bridge)

LIGHTING

rubber mounted LED lights 2 tail light package with aluminum cover 2 clearance lights per side 1 mid-turn light per side 7 pole electric socket

12V sealed Grote harness

PAINT

black, IH red, CAT yellow air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

5 year structural 1 year paint

AVAILABLE MODELS

XL 80 HDE XL 90 HDE other custom cap

other custom capacities also available, ask your sales representative for details standard features vary with custom units